

Bond

BONDFLAKE

Bond

BONDFLAKE

Product Description

BondFlake is a decorative seamless, multi-coloured fantasy flooring system. This system requires minimum maintenance. It provides an extremely durable flooring surface. It is UV resistant and chemical resistant.

Feature & Benefits

- Easy application with minimal disruption
- Eliminates the arduous task of hacking
- Finished surface is fuel, oil, diesel, water and chemical resistant

Application Range

- Corridors;
- Pavements;
- Lift Lobbies;
- Staircases;
- Void Deck; etc.

Specification Clause

The solvent free epoxy system shall be **BondFlake** – supplied by **B-Team Construction Supplies Pte Ltd**.

Application Notes

Substrate Preparation

The substrate must be free from all contaminants (dust, oil, grease) and all loose materials must be removed and cleaned. It is advisable that the entire floor has to be washed clean by high pressure water jetting with clean water to remove contaminants, loose materials and dust.

Priming

Prime with **BF Primer**

Installation

After Self Levelling is done, apply one coat of Mackincote BF Primer and broadcast the colour flakes on the surface.

Allow Mackincote BF to dry for at least 4-6 hours before sweeping away the surplus colour-flakes.

Apply one coat of **Mackincote Epoxy**, allow 4-6 hours to dry. Sand smooth the colour flakes after drying. Followed by one coat of **Mackincote PU54 Clear Finish** to the colour-flakes surface.

Allow 24 hours to dry.